

34 SCFM






Type A-1

PLUG (STEEL)	AUTOMATIC COUPLER (STEEL)	MANUAL COUPLER (STEEL)	MANUAL COUPLER (BRASS)
-----------------	---------------------------------	------------------------------	------------------------------

One Way Shut-Off






FEMALE THREAD





	Part No.	Part No.	Part No.	Part No.
1/8" (F) NPT	17.1122	17.1422	17.1722	17.1723
1/4" (F) NPT	17.1142	17.1442	17.1742	17.1743
3/8" (F) NPT	-	17.1462	17.1762	17.1763

MALE THREAD



	Part No.	Part No.	Part No.	Part No.
1/8" (M) NPT	17.1222	17.1522	17.1822	17.1823
1/4" (M) NPT	17.1242	17.1542	17.1842	17.1843
3/8" (M) NPT	-	17.1562	17.1862	17.1863

HOSE BARB



	Part No.	Part No.	Part No.	Part No.
1/4" I.D.	17.1342	17.1642	17.1942	17.1943
5/16" I.D.	17.1352	17.1652	17.1952	17.1953
3/8" I.D.	17.1362	17.1662	17.1962	17.1963

2 OR 4 PIECE KIT



Part No.	Description
17.1711	2 piece kit (17.1242 + 17.1742)
17.1704	4 piece kit (17.1142 + 17.1242 + 17.1742 + 33.1128)

ADJUSTABLE POCKET BLOW GUN



Part No. 65.1017

Applications

- Ideal for : Air tools
- Vacuum
- Water

Features

- Interchangeable with 1/4" ARO Type plugs
- Corrosion resistant

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)

Air Flow

34 SCFM

Construction

Body : Steel

Sleeve and Valve Spring : Stainless Steel

Seal : Buna-N

Locking Balls : Stainless Steel

Socket Sleeve : Steel

Features

- Quickly transforms a Type A-1 coupler into an adjustable blow gun
- Blow pressure easy to adjust by rotating spout
- Maximum inlet pressure 150 PSI

Series 17


Quick Couplers Type A-2 (ARO 3/8")



One Way Shut-Off



60 SCFM



Type A-2

PLUG
(STEEL)

AUTOMATIC
COUPLER
(STEEL)

Applications

- Ideal for : Air tools
- Vacuum
- Water

Features

- Interchangeable with 3/8" ARO Type plugs
- Corrosion resistant

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)



Air Flow

34 SCFM

Construction

Body : Steel
Sleeve and Valve Spring : Stainless Steel
Seal : Buna-N
Locking Balls : Stainless Steel
Socket Sleeve : Steel

FEMALE THREAD



Part No.



Part No.

3/8" (F) NPT

17.2162

17.2462

MALE THREAD



Part No.


Part No.

3/8" (M) NPT

17.2262

17.2562

HOSE BARB



Part No.

3/8" I.D.

17.2362

For any questions
or information about
compressed air
you may contact us at
Tel. : **1-888-730-0501**
Fax : **1-888-730-3522**
or visit our web site at
www.airmax.ca