


32 SCFM



Type L-1

One Way Shut-Off



PLUG
(STEEL)

**AUTOMATIC
COUPLER**
(STEEL)

**MANUAL
COUPLER**
(BRASS)



FEMALE THREAD



Part No.

Part No.

Part No.



1/4" (F) NPT

19.1142

19.1442

19.1743

MALE THREAD



Part No.

Part No.

Part No.

1/4" (M) NPT

19.1242

19.1542

19.1843

2 OR 4 PIECE KIT



Part No.

Description

19.1711

2 piece kit
(19.1242 + 19.1442)

19.1704

4 piece kit
(19.1142 + 19.1242 +
19.1442 + 33.1128)

Applications

- Ideal for air tools

Features

- Interchangeable with 1/4" Lincoln Type plugs
- Automatic
- Full length plug

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)

Air Flow

32 SCFM

Construction

Body : Steel

Sleeve and Valve Spring : Stainless Steel


Seal : Buna-N

Locking Balls : Stainless Steel

ADJUSTABLE POCKET BLOW GUN

Features

- Quickly transforms a Type L-1 coupler into an adjustable blow gun
- Blow pressure easy to adjust by rotating spout
- Maximum inlet pressure 150 PSI



Part No. 65.1019

