


32 SCFM



Type L-1

One Way Shut-Off



PLUG
(STEEL)

**AUTOMATIC
COUPLER**
(STEEL/BRASS)

**MANUAL
COUPLER**
(STEEL/BRASS)





FEMALE THREAD




	Part No.	Part No.	Part No.
1/8" (F) NPT	19.1122	---	19.1722
1/4" (F) NPT	19.1142	19.1442	19.1742
3/8" (F) NPT	19.1162	---	19.1762

MALE THREAD



	Part No.	Part No.	Part No.
1/8" (M) NPT	19.1222	---	19.1822
1/4" (M) NPT	19.1242	19.1542	19.1842
3/8" (M) NPT	19.1262	---	19.1862

HOSE BARB



	Part No.	Part No.	Part No.
1/4" (M) NPT	---	19.1642	19.1942
3/8" (M) NPT	---	19.1662	19.1962



2 OR 4 PIECES KIT

Part No.	Description
19.1711	2 pieces kit (19.1242 + 19.1442)
19.1704	4 pieces kit (19.1142 + 19.1242 + 19.1442 + 33.1128)

Applications

- Ideal for air tools

Features

- Interchangeable with 1/4" Lincoln Type plugs
- Automatic
- Full length plug

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)

Air Flow

32 SCFM

Construction

Body : Steel

Sleeve and Valve Spring : Stainless Steel

Seal : Buna-N

Locking Balls : Stainless Steel

ADJUSTABLE POCKET BLOW GUN



Part No. 65.1019

Features

- Quickly transforms a Type L-1 coupler into an adjustable blow gun
- Blow pressure easy to adjust by rotating spout
- Maximum inlet pressure 150 PSI