



## MALE CONNECTOR




Part No.	Tube O.D. in.	Thread (M) NPT in.
34.1114	1/8	1/8
34.1142	3/16	1/8
34.1154	1/4	10-32
34.1156	1/4	1/8
34.1158	1/4	1/4
34.1162	1/4	3/8
34.1168	5/16	1/8
34.1170	5/16	1/4
34.1180	3/8	1/8
34.1182	3/8	1/4
34.1184	3/8	3/8
34.1194	1/2	3/8
34.1196	1/2	1/2

## FEMALE CONNECTOR




Part No.	Tube O.D. in.	Thread (F) NPT in.
34.1256	1/4	1/8
34.1258	1/4	1/4
34.1268	5/16	1/8
34.1282	3/8	1/4
34.1294	1/2	3/8

## MALE ELBOW




Part No.	Tube O.D. in.	Thread (M) NPT in.
34.1314	1/8	1/8
34.1342	3/16	1/8
34.1356	1/4	1/8
34.1358	1/4	1/4
34.1362	1/4	3/8
34.1368	5/16	1/8
34.1380	3/8	1/8
34.1382	3/8	1/4
34.1384	3/8	3/8
34.1394	1/2	3/8
34.1396	1/2	1/2

## EXTENDED MALE ELBOW




Part No.	Tube O.D. in.	Thread (M) NPT in.
34.1458	1/4	1/4

## MALE BRANCH TEE




Part No.	Tube 1 & 2 O.D. in.	Thread (M) NPT in.
34.1556	1/4	1/8
34.1558	1/4	1/4
34.1580	3/8	1/8
34.1582	3/8	1/4

## MALE RUN TEE



Part No.	Tube 1 & 2 O.D. in.	Thread (M) NPT in.
34.1658	1/4	1/4
34.1682	3/8	1/4

## FEMALE ELBOW



Part No.	Tube O.D. in.	Thread (F) NPT in.
34.1756	1/4	1/8
34.1758	1/4	1/4
34.1782	3/8	1/4
34.1794	1/2	3/8



## Applications

- Made for compressed air tubing, water and systems under heavy vacuum applications
- Used in industrial assemblies, machinery and various equipment

## Features

- Interchangeable with Poly-Flo and Poly-Tite fittings
- Teflon coated male threads
- Reusable and quick connections
- Integrated nut and socket for tightening
- May be connected and disconnected repetitively while keeping its quality and efficiency

## Specifications

**Maximum Working Pressure**  
150 PSI

**Working Temperature**  
-40°C to 79°C (-40°F to 175°F)  
for tubing 1/8" to 3/8" I.D.  
-40°C to 60°C (-40°F to 140°F)  
for tubing 1/2" I.D.

**Construction**  
Body: Brass

**Recommended Tubing**  
- Polyethylene Tubing (Series 40)

- Nylon Tubing (Series 40)


- Polyurethane Tubing (Series 40)



# Series 34


## Compression Brass Push-Type Fittings for Plastic Tubing

### STRAIGHT UNION




Part No.	Tube 1 O.D. in.	Tube 2 O.D. in.
34.2114	1/8	1/8
34.2144	3/16	3/16
34.2158	1/4	1/4
34.2172	5/16	5/16
34.2182	3/8	1/4
34.2184	3/8	3/8
34.2196	1/2	1/2

### BULKHEAD UNION




Part No.	Tube 1 O.D. in.	Tube 2 O.D. in.
34.2258	1/4	1/4
34.2284	3/8	3/8

### BULKHEAD UNION CONNECTOR



Part No.	Tube 1 O.D. in.	Tube 2 O.D. in.
34.2358	1/4	1/4

### UNION TEE



Part No.	Tube 1 O.D. in.	Tube 2 O.D. in.	Tube 3 O.D. in.
34.2514	1/8	1/8	1/8
34.2558	1/4	1/4	1/4
34.2572	5/16	5/16	5/16
34.2584	3/8	3/8	3/8
34.2596	1/2	1/2	1/2

### PLASTIC SLEEVE



Part No.	Tube O.D. in.
34.2658	1/4
34.2672	5/16
34.2684	3/8
34.2696	1/2

### NUT



Part No.	Tube O.D. in.
34.2714	1/8
34.2758	1/4
34.2772	5/16
34.2784	3/8
34.2796	1/2

### UNIVERSAL NUT AND BRASS SLEEVE ASSEMBLY



Part No.	Tube O.D. in.
34.2814	1/8
34.2844	3/16
34.2858	1/4
34.2872	5/16
34.2884	3/8
34.2896	1/2

### NUT AND PLASTIC SLEEVE ASSEMBLY



Part No.	Tube O.D. in.
34.2958	1/4
34.2972	5/16
34.2984	3/8
34.2996	1/2