


3 way / 2 position



SINGLE AIR PILOT VALVE 3 WAY/2 POSITION



Part No.	Thread (F) NPT	CV
79.1110	1/8	0.65
79.1120	1/4	1.08
79.1130	3/8	2.30
79.1140	1/2	3.50

DOUBLE AIR PILOT VALVE 3 WAY/2 POSITION



Part No.	Thread (F) NPT	CV
79.1210	1/8	0.65
79.1220	1/4	1.08
79.1230	3/8	2.30
79.1240	1/2	3.50

Features

- Pneumatic piloted aluminum valve
- Available in single or double air piloted valve configurations

Specifications

Maximum Working Pressure

150 PSI

Working Temperature

-10°C to 50°C (14°F to 122°F)




SINGLE AIR PILOT VALVE 5 WAY/2 POSITION



Part No.	Thread (F) NPT	CV
79.2110	1/8	0.55
79.2120	1/4	1.00
79.2130	3/8	2.72
79.2140	1/2	4.44

DOUBLE AIR PILOT VALVE 5 WAY/2 POSITION



Part No.	Thread (F) NPT	CV
79.2210	1/8	0.55
79.2220	1/4	1.00
79.2230	3/8	2.72
79.2240	1/2	4.44

Features

- Pneumatic piloted aluminum valve
- Air pressure operated spool
- Single or double acting

Specifications

Maximum Working Pressure

150 PSI

Working Temperature

-10°C to 50°C (14°F to 122°F)

DOUBLE AIR PILOT VALVE CLOSED CENTER 5 WAY/3 POSITION



Part No.	Thread (F) NPT	CV
79.2310	1/8	0.55
79.2320	1/4	1.00
79.2330	3/8	2.72
79.2340	1/2	4.44